

888.372.1888  
www.earphoneconnect.com  
25139 Avenue Stanford  
Valencia, CA 91355

EARPHONE  
CONNECTION

FOLLOW US

FACEBOOK • INSTAGRAM • TWITTER • YOUTUBE



# COMBI COMBO WIRELESS PTT SURVEILLANCE KIT

INNOVATIVE HANDS-FREE COMMUNICATIONS...The **COMBI COMBO** combines our two best-selling earpieces with the new COMBI Wireless Easy-Connect Adapter Receiver & Wireless PTT Button Transmitter. With the Combi Combo, you have the benefit of combining hands-free technology with both our #1 selling **Hawk Lapel Microphone** patrol kit and our **iBlend Covert Surveillance Kit**. The wireless PTT transmitter button can be attached to your finger, a handle-bar or pistol grip for hands-free operations. You can also attach additional EPC accessories, so the Combi Combo is versatile, serving a variety of law enforcement divisions; patrol, undercover, or tactical.



## FEATURES & BENEFITS:

- ▶ **ALWAYS ON!** Easy-Connect Adapter Receiver pairs via one-to-one.
- ▶ **Two Versatile Microphone Kits included:**
  - Our popular **Hawk Lapel Microphone** with long tube earpiece, whisper-sensitive microphone & easy-to-grip PTT.
  - The **Covert iBlend Surveillance Kit** with iPod-style earbuds & inline microphone.
- ▶ Wireless push-to-talk (PTT) Transmitter button can be attached to any handle bar, finger, or pistol grip. No Batteries to Charge!

### KIT INCLUDES:

#### WIRELESS PTT FINGER TRANSMITTER



- ✓ 100,000 Presses
- ✓ Submersible

#### EASY-CONNECT ADAPTER RECEIVER



#### OPTION 1



#### OPTION 2



EASY  
CONNECT  
ADAPTER  
RECEIVER  
(ADAPTER  
WILL VARY)

#### WIRELESS PTT \*\*TRANSMITTER BUTTON



- ▶ The kit comes equipped with the patented Fin Ultra™ ear tip for all day comfort and enhanced acoustical engineering for a higher level of situational awareness.



### TECHNICAL SPECIFICATIONS

RECEIVER (ADAPTER)		TRANSMITTER (REMOTE PTT)	
WORKING VOLTAGE	DC 3.3V ~ 5.5V	WORKING VOLTAGE	DC3V (CR2032 battery)
WORKING CURRENT	<30mA	WORKING CURRENT	<30mA
WORKING FREQUENCY	2.4GHz	QUIESCENT CURRENT	<1µA
COMMUNICATION RATE	50KBps	WORKING FREQUENCY	15.5mm x 4.8mm
SENSITIVITY	-102dBm	COMMUNICATION RATE	50KBps
TRANSMITTER POWER	-6dBm (50ohm input)	SENSITIVITY	-102dBm
COMMUNICATION DISTANCE	>10m	TRANSMITTER POWER	-6dBm (50ohm input)
PCBA SIZE	24mm x 9.5mm	COMMUNICATION DISTANCE	>10m
		PCBA SIZE	24mm x 9.5mm